

## E-Pure-L

Ageing, cooling and red wine serving cabinet  
3 temperatures

Access pack

Standard shelves



Sliding shelf  
ACMS



Storage shelf  
AXUH

« Premium » shelves



Sliding shelves

ACMS2B

ACMS2W



Storage shelves  
AXUH2B



Storage shelves  
AXUH2W

ORIGINE  
FRANCE®  
GARANTIE

BVCert. 6010761



### GENERAL FEATURES

|                                       | Full Glass door                 | Black Piano                     |
|---------------------------------------|---------------------------------|---------------------------------|
| Gross weight packaged (kg)*           | 119                             | 112                             |
| Empty wine cabinet net weight (kg)    | 103                             | 96                              |
| Equipped wine cabinet net weight (kg) | 116,8                           | 110,8                           |
| Dimensions H x W x D (mm)             | 1825 x 680 x 715                | 1825 x 680 x 715                |
| Dimensions in pack H x W x D (mm)     | 1950 x 720 x 760                | 1950 x 720 x 760                |
| Colors / finishes                     | Nero, Buffle or Ostrich leather | Nero, Buffle or Ostrich leather |

### TECHNICAL FEATURES

#### REGULATION

- Electronic regulation
- Temperature setting range from 15 to 22°C (upper compartment) and 9 to 15°C (ageing area)
- LED screen with touch buttons
- Electronic inner display and settings – digital screen
- Temperature visualisation
- Visual alarms in case of disfunctioning (open door, sensor fault, temperature alarm, charcoal filter)
- Automatic defrost

#### HOT – COLD – INSULATION TECHNOLOGIES

|                            |   |
|----------------------------|---|
| Cold production:           | • Static<br>• Compressor R600a/R134a    |
| Cords:                     | • CE/UK/JA/AU/CH/CN/US                  |
| Hot production:            | • Heating element                       |
| Hot release:               | • Automatic<br>• Threshold : adjustable |
| Inner material:            | • Aluminium                             |
| Exterior coating material: | • HDF (High Density Fiber)              |
| Insulation type:           | • PU foam (59 mm)                       |

### EQUIPMENTS & ACCESSORIES

#### EQUIPMENT

- On/ Off button
- Full Glass door, Black Piano door, Glass door, Stainless steel Glass door, Silver Glass door
- Inner lighting (3 options: permanent, open door, disabled)
- Optional light band, to order
- Charcoal filter (with meter)
- Front adjustable feet
- Removable handle with glass finishing and centered lock (Full Glass and Black Piano doors only)
- Humidity collector rearward

#### ACCESSORIES

- 3 sliding shelves and 3 storage shelves
- Overall capacity: 190 bottles\*\*
- Sliding shelf capacity: up to 12 bottles
- Storage shelf capacity: up to 77 bottles
- « Premium » sliding shelves equipped with a brake
- NB: rise of the space between shelf support strips by 5,4 mm (labels preservation and convenient champagne bottles positioning )
- 6 removable bottles identifiers per « Premium » shelf
- 1 erasable felt-tip marker per batch of « Premium » shelves
- 1 EuroCave key ring (Full Glass and Black Piano doors only)

### ENERGY EFFICIENCY AND CONSUMPTION

| Wiring                                      | 230V-50Hz (R600a gas) |            | 115V-60Hz (R134a gas) |            |
|---|-----------------------|------------|-----------------------|------------|
|   | Black Piano           | Full Glass | Black Piano           | Full Glass |
| Doors type                                  |                       |            |                       |            |
| Energy efficiency rating                    | A+                    | A          | /                     | /          |
| Annual energy consumption Aec (kWh/year)*** | 128                   | 165        | 183                   | 256        |
| Acoustic emissions (dB(A))                  | 37                    | 37         | 38                    | 38         |

|                                       |                    |
|---------------------------------------|--------------------|
| Useful volume (L)                     | 450                |
| Temperature of the upper compartments | 15-22°C<br>59-77°F |